

# The Motorcraft® Battery Product Line

Complete attention to customer satisfaction and world class efficiency!

Motorcraft batteries cover automotive, commercial, industrial and specialty applications.

**Ask your Motorcraft® Retailer for details.**

## BATTERY SPECIFICATION CHART

BCI/ DIN	Motorcraft® Part Number	Cold Cranking AMPS (At 0° F)	Reserve Capacity (Minutes)	Maximum Dimensions Inches (mm)			Approx. Weight (Wet)
				Length	Width	Height	LBS. (KG)
<b>TESTED TOUGH MAX</b>							
<b>12-Volt Post Terminals</b>							
24	BXT-24-A	700	130	10.94 (278)	6.85 (174)	8.70 (221)	42 (19.1)
24F	BXT-24F-B	750	130	10.2 (260)	6.6 (169)	8.7 (222)	44 (20.0)
27	BXT-27-B	810	140	12.72 (323)	6.85 (174)	8.70 (221)	50 (22.5)
27F	BXT-27F-A	710	165	12.72 (323)	6.85 (174)	8.70 (221)	42 (19.1)
34	BAGM-34	740	115	11.00 (278)	6.8 (174)	7.8 (199)	43 (19.3)
34	BXT-34-B	800	110	10.94 (278)	6.89 (175)	7.80 (198)	37 (16.8)
35	BAGM-35	650	100	9.7 (245)	6.8 (174)	8.8 (225)	42 (19.0)
35	BXT-35-A	640	100	8.98 (228)	6.85 (174)	8.82 (224)	37 (16.8)
36R	BXT-36R	650	130	10.24 (260)	7.17 (182)	7.80 (198)	39 (17.8)
40R	BXT-40R	590	105	10.91 (277)	6.85 (174)	6.89 (175)	37 (16.8)
47/H5	BXT-47H5	650	100	9.53 (242)	6.89 (175)	7.48 (190)	33 (14.9)
48/H6	BEF-48H6	700	120	10.9 (278)	6.9 (175)	7.5 (190)	45 (20.4)
48/H6	BXT-48H6-610	610	110	10.94 (278)	6.89 (175)	7.48 (190)	38 (17.6)
48	BAGM-48H6-760	760	120	10.94 (278)	6.89 (175)	7.48 (190)	47 (21.1)
49/H8	BAGM-49H8	850	160	13.94 (354)	6.89 (175)	7.48 (190)	59 (26.6)
51R	BXT-51R	500	85	9.38 (238)	5.06 (129)	8.82 (224)	27 (12.2)
56	BXT-56-A	590	95	10.20 (259)	6.02 (153)	8.31 (211)	33 (15.0)
58	BXT-58-A	550	80	10.04 (255)	7.20 (183)	6.85 (174)	29 (13.2)
58R	BXT-58R-A	610	100	10.04 (255)	7.20 (183)	6.85 (174)	31 (14.1)
59	BXT-59	540	100	10.04 (255)	7.48 (190)	7.64 (194)	34 (15.5)
65	BAGM-65	750	120	12 (306)	7.6 (192)	7.6 (192)	45 (20.0)
65	BXT-65-650	650	130	12.05 (306)	7.48 (190)	7.64 (194)	42 (19.1)
65	BXT-65-750	750	140	12.05 (306)	7.48 (190)	7.64 (194)	45 (20.6)
65	BXT-65-850	850	150	12.05 (306)	7.48 (190)	7.64 (194)	46 (20.9)
66	BXT-66-750	750	140	12.05 (306)	7.44 (189)	7.64 (194)	45 (20.6)
67R	BXT-67R	390	65	8.27 (210)	6.89 (175)	6.89 (175)	28 (12.7)
90	BXT-90T5-590	590	90	9.53 (242)	6.89 (175)	6.89 (175)	32 (14.5)
90	BXT-90T5-500	500	85	9.53 (242)	6.89 (175)	6.89 (175)	30 (13.7)
94R/H7	BXT-94RH7-730	730	140	12.40 (315)	6.89 (175)	7.48 (190)	45 (20.5)
94R/H7	BAGM-94RH7-800	800	140	12.40 (315)	6.89 (175)	7.48 (190)	50 (22.9)
95R/H9	BAGM-95RH9	950	190	15.5 (394)	6.9 (175)	7.5 (190)	64.5 (29.3)
96R	BAGM-96R	590	80	9.5 (242)	6.9 (175)	6.9 (175)	33 (15.2)
96R	BXT-96R-500	500	85	8.98 (228)	6.85 (174)	6.89 (175)	30 (13.7)
96R	BXT-96R-590	590	90	8.98 (228)	6.85 (174)	6.89 (175)	32 (14.5)
99R	BXT-99RT4-A	470	65	8.27 (210)	6.89 (175)	6.89 (175)	30 (13.6)
124R	BXT-124R	700	120	10.31 (262)	6.97 (177)	8.58 (218)	39 (17.7)

**NOTE:** Battery specifications are subject to change without notice.

## BATTERY SPECIFICATION CHART – CONT'D

BCI/ DIN	Motorcraft® Part Number	Cold Cranking AMPS (At 0° F)	Reserve Capacity (Minutes)	Maximum Dimensions Inches (mm)			Approx. Weight (Wet)
				Length	Width	Height	LBS. (KG)
<b>TESTED TOUGH MAX – Cont'd</b>							
<b>12-Volt Side Terminals</b>							
75	BXT-75-A	700	95	9.69 (246)	7.64 (194)	7.20 (183)	32 (14.6)
78	BXT-78	800	110	10.94 (278)	7.64 (194)	7.44 (189)	38 (17.0)
79	BXT-79	840	140	12.09 (307)	7.05 (179)	7.40 (188)	43 (19.5)
<b>12-Volt Dual Terminals</b>							
3478DT	BXT-3478	800	115	10.98 (279)	7.24 (184)	8.98 (228)	39 (17.6)
<b>TESTED TOUGH PLUS</b>							
<b>12-Volt Post Terminals</b>							
24F	BXL-24F-A	600	110	10.94 (278)	6.85 (174)	8.70 (221)	40 (18.1)
26	BXL-26	525	81	8.70 (221)	6.77 (172)	7.80 (198)	30 (13.6)
34	BXL-34	685	120	10.94 (278)	6.89 (175)	7.80 (198)	37 (16.8)
35	BXL-35-A	500	80	8.98 (228)	6.85 (174)	8.82 (224)	34 (15.5)
36R	BXL-36R	650	130	10.25 (260)	7.18 (182)	7.80 (198)	39 (17.7)
40R	BXL-40R	650	120	10.91 (277)	6.85 (174)	6.89 (175)	36 (16.5)
51	BXL-51-A	500	85	9.37 (238)	5.06 (129)	8.82 (224)	28 (12.6)
58	BXL-58-A	550	80	10.04 (255)	7.20 (183)	6.85 (174)	28 (12.7)
58R	BXL-58R-B	610	100	10.04 (255)	7.20 (183)	6.85 (174)	33 (15.0)
59	BXL-59	540	100	10.04 (255)	7.48 (190)	7.63 (194)	34 (15.5)
65	BXL-65	675	130	12.05 (306)	7.48 (190)	7.63 (194)	41 (18.5)
86	BXL-86	525	90	9.06 (230)	6.82 (173)	8.00 (203)	35 (16.0)
96R	BXL-96R-A	500	90	8.98 (228)	6.30 (160)	6.89 (175)	33 (15.0)
121R	BXL-121R	600	100	8.19 (208)	6.97 (177)	8.46 (215)	31 (13.9)
<b>FLEET TOUGH / COMMERCIAL SERIES</b>							
<b>12-Volt</b>							
4D	BH-4DW	1000	295	20.90 (531)	8.27 (210)	9.57 (243)	98 (44.2)
8D	BH-8DW	1155	380	20.69 (526)	10.98 (279)	9.60 (244)	124 (56.2)
50	BH-50	600	108	13.2 (334)	5.3 (134)	10 (254)	46 (20.9)
<b>12-Volt Auxiliary</b>							
N/A	BHAGM-AUX1-A	100	7.5 Ah	5.9 (149.9)	3.45 (87.7)	4.15 (105.5)	7.24 (3.29)
N/A	BHAGM-AUX1-B	90	6	5.3 (135)	3.0 (75)	4.8 (122)	6 (2.8)
<b>FLEET TOUGH / EXTRA</b>							
<b>12-Volt</b>							
31	BH-31-XL	750	180	12.99 (330)	6.77 (172)	9.33 (237)	57 (25.9)
31	BH-31-XT	900	195	12.99 (330)	6.77 (172)	9.33 (237)	61 (27.7)
31	BH-31P-XT	900	195	12.99 (330)	6.77 (172)	9.33 (237)	60 (27.2)
31	BHAGM-31	825	200	12.99 (330)	6.77 (172)	9.33 (237)	70.8 (32.1)
H3	BHAGM-H3	380	60	6.9 (175)	6.9 (175)	7.5 (190)	27 (12.1)
48	BH-48H6-730A	730	115	10.9 (278)	6.9 (175)	7.5 (190)	39 (17.6)
48/H6	BHEF-48H6	700	120	10.9 (278)	6.9 (175)	7.5 (190)	45 (20.3)
49	BH-49H8	900	150	13.94 (354)	6.89 (175)	7.48 (190)	48 (21.8)
65	BH-65-HH	750	140	12.05 (306)	7.48 (190)	7.63 (194)	42 (19.1)
101	BH-101	650	110	10.20 (260)	7.00 (179)	6.70 (170)	36 (16.2)
<b>GOLF CAR / UTILITY</b>							
<b>6-Volt</b>							
GC2	BH-GC2-B	107 MIN. @ 75 AMPS		10.20 (259)	7.05 (179)	11.19 (284)	62 (28.2)

NOTE: Battery specifications are subject to change without notice.

Chart last updated: August 2020